




KANTELCONTAINER

Tuinbouwtechniek
& -benodigheden



TKB



TKB

	volume m ³	A mm	B m	C	D mm	E m	F	G	H mm	mass g	load cg empty mm	load cg full mm	load cap. kg
TKB 500	0,50	1240	1400	1014	120	70	180	0	100	55	600	615	3000
TKB 600	0,60	1240	1400	1014	120	83	180	0	100	62	600	620	3000
TKB 700	0,70	1240	1400	1014	120	94	180	0	100	70	590	615	3000
TKB 750	0,75	1240	1400	1014	120	1010	180	200	100	174	590	6	3000
TKB 800	0,80	1240	1400	1014	120	070	576	200	100	78	590	620	3000
TKB 900	0,90	1240	1400	1014	120	191	576	200	100	90	590	625	3000
TKB 1000	1,00	1240	1400	1014	120	312	576	200	100	98	590	630	3000
TKB 1200	1,20	1240	400	1014	120	1555	6	200	100	213	580	625	3000
TKB 1500	1,50	1240	1400	1014	120	919	576	200	100	235	580	635	3000
TKB 2000	2,00	1400	1540	115	230	2100	576	200	100	281	630	690	3000
TKB 3000	3,00	1800	2150	1450	315	760	576	200	100	320	860	950	3000
TKB 3500	3,50	1800	2150	1450	315	2050	576	200	100	361	860	950	3000
TKB 5000	5,00	1800	2150	1450	315	2950	576	200	100	450	850	950	3000
TKB 600 S	0,60	1100	1240	900	80	1100	576	200	100	182	540	565	3000
TKB 800 S	0,80	1240	1440	1040	120	100	576	200	100	2 1	600	640	3000
TKB 1000 S	1,00	1400	1540	1100	315	100	576	200	100	2 8	670	715	3000
TKB 1200 S	1,20	1400	1690	1200	315	100	576	200	100	229	700	750	3000


DETAILS




Safeguards
Beveiliging
Sicherung
Dispositivo de seguridad



Top rim 50x30 mm all round
Bovenrand rondom 50x30 mm
Oberkante rundum 50x30 mm
Perfi l por el borde 50x30 mm



Bin to base latch
Vergrendeling kuip / onderstel
Verriegelung Behälter / Rahmen
Dispositivo de inmovilización
contenedor / bastidor



Tipping system bin / base
Kantelsysteem
kuip / onderstel
Kippsystem Behälter /
Rahmen
Sistema basculante contenedor /bastidor



Manual pallet truck pick up
Opname handpallettruck
Aufnahme mit Handhubwagen
Montaje a transpaleta manual



KaRo BV
Tulpenmarkt 4
1681 PK Zwaagdijk

T 0228 - 56 31 35
E info@karobv.nl
www.karobv.nl



OPTION S



Cover
Deksel
Deckel
Tapa




Extended sides
Opgehoogde wanden
Erhöhte Seitenwände
Paredes laterales más altas



Automatic tipping system
Automatisch kantelsysteem
Automatisches Kippsystem
Sistema basculante automático



Rubber, Vulkollan, nylon wheels
Rubberen, vulkollan, nylon wielen
Rollen aus Gummi, Vulkollan, Nylon
Ruedas de caucho, Vulkollan, nylon



Fork latch
Vorkvergrendeling
Gabelverriegelung
Fijación de las horquillas



Sieve bottom and drain tap
Zeefbodem + aftapkraan
Siebboden und Ablasshahn
Fondo tamizado + llave de purga

HEAVY DUTY OPTIONS



6-8 mm steel plate
6-8 mm plaatstaal
6-8 mm Stahlblech
Chapa de acero 6-8 mm



Double hook latch
Dubbele haaksluiting
Doppelter Hakenverschluss
Doble gancho de cierre



Guides
Geleiding
Führungsschiene
Guía



- The most common tipping
- Guided tipping system at the front, after emptying bin falls safely back onto the latch
- Side thickness of bin 3 mm



- Gängigster Kippcontainer
- Stufenloses Kippsystem an der Vorderseite, fällt nach der Entleerung auf sichere Weise in die Verriegelung zurück
- Wandstärke des Behälters 3 mm



- De meest gangbare kantelcontainer
- Geleidelijk werkend kantelsysteem aan voorzijde, valt na lediging veilig terug in de vergrendeling
- Wanddikte kuip 3 mm



- El contenedor basculante más común
- Sistema basculante de funcionamiento gradual en la parte frontal, regresa sin problemas al dispositivo de inmovilización después del vaciado
- Grosor de las paredes del contenedor 3 mm



KaRo BV
Tulpenmarkt 4
1681 PK Zwaagdijk

T 0228 - 56 31 35
E info@karobv.nl
www.karobv.nl

