



AMS MF
AMS PH
AMS RH

- Foot mounted, with display
- Microprocessor technology
- Manual stroke length adjustment
- Manual venting PVDF pump head
- All liquid ends (pump head, injection valve, foot filter, delivery hose) are in PVDF
- PP pump head and accessories (with PE hose) available on request

MODEL	AMS MF	AMS PH	AMS RH
CODE	AMF	APH	ARH
Dosing system	Constant/Proportional	Proportional	Proportional
Level control	●	●	●
Flow sensor input	●		
Stand-by input	●		
Alarm output	●	optional (+ € 30,00)	optional (+ € 30,00)
Functions	<ul style="list-style-type: none"> • MULTIFUNCTION (Constant, Divide, Multiply, PPM, Batch, Volt, mA, %, ml/q) • Set AUTOMATIC REPRIMING, with a flow sensor installed. • Set STROKES RECOVERY SYSTEM, with a flow sensor installed. • Set UPKEEP DOSING MODE in plant shutdown situation. • WORK-PAUSE MODE: cyclic dosing controlled by an external contact. 	PH meter (0-14) - supplied without pH probe	ORP meter (0-2000mV) - supplied without ORP probe

FLOW						PRICE			PUMP HEAD (option)		HOSE (suct./outgas.)
Pressure bar	Flow l/h	cc/S	PVDF pump head	PVDF injection hose	Suction hose	AMS MF	AMS PH	AMS RH	PMMA	SS ¹	PVDF
25	05	0,70	L	4 x 6	4 x 6						
15	10	1,4	M	4 x 6	4 x 6						
10	15	2,1	M	6 x 8	6 x 8						
07	20	2,8	N	6 x 8	6 x 8						
03	40	5,6	S	8 x 10	8 x 12						
02	60	7,7	T	8 x 10	8 x 12						

SS ACCESSORIES ¹	
Pump head	Fittings
Li	3/8"
Mi	1/2"
Ni	1/2"
Si	3/4"
Ti	3/4"

¹ Specify on order, the external thread of the valves: conical, cylindrical or NPT.

Stainless Steel pump does not fit installation kit (accessories and hoses).



KaRo BV
Tulpenmarkt 4
1681 PK Zwaagdijk

T 0228 - 56 31 35
E info@karobv.nl
www.karobv.nl

