

Pulspomp Prisma

Tuinbouwtechniek
& -benodigheden



Productinfo

FEATURES

- ➔ Foot mounted, with display
- ➔ **Stepper motor-driven** diaphragm dosing pump, mechanical actuated
- ➔ **Turndown ratio 1:4800**
- ➔ **Slow suction modes (4x)** for viscous media
- ➔ Color status display
- ➔ Power supply 110 – 240 V, 50/60 Hz
- ➔ Manual degassing valve (PVDF and PP pump heads)
- ➔ Double ball check valve



FUNCTIONS

MODELS	PRISMA
Dosing system	Constant/Proportional
Level control	●
Stand-by input	●
Alarm output	●
Functions	<ul style="list-style-type: none"> • SLOW SUCTION MODE • TURNDOWN RATIO 1:4800 • MULTIFUNCTION (Constant, Constant with external input, ppm, %, mlq, Pause-work, Weekly, mA, Pulse, Volt, external Batch and manual Batch) • External constant dosing • Multicolor display: pump running (green); stand-by (white); warning condition (yellow); alarm condition (red)
MODBUS	optional

PRICES

FLOW					PRICES ²	Pump head (options)		HOSE (suct./outgas.)
Pressure bar	Capacity l/h	PVDF pump head	PVDF injection hose	Suction hose	PRISMA	PMMA	SS ¹	PVDF
20	5	L	4 x 6	4 x 6				
10	13	M	6 x 8	6 x 8				
5	28	N	8 x 10	8 x 12				
2	80	N	8 x 10	8 x 12				

SS ACCESSORIES ¹	
Pump head	Fittings
Li	3/8"
Mi	1/2"
Ni	1/2"

¹ Specify on order, the external thread of the valves: conical, cylindrical or NPT.
Stainless Steel pump does not fit installation kit (accessories and hoses).

² Extraprice MODBUS



KaRo BV
Tulpenmarkt 4
1681 PK Zwaagdijk

T 0228 - 56 31 35
E info@karobv.nl
www.karobv.nl

